

AX104696 Cable Assemblies - Breakout Kit - 12-Fiber

Preview Document. Not Live Data.



For more Information
please call

1-800-Belden1

Description

BREAKOUT KIT FOR 5.2MM SUBUNITS (CENTRAL TUBE), 12-FIBER, 1-PACK

Usage (Overall):

Suitable Applications	Data Centers, Main Equipment Rooms, Telecommunications Rooms
Related Parts	Brilliance, Optimax, Central Loose Tube Fiber Cables

Physical Characteristics (Connectivity):

Weight:

Weight:	0.500 lbs.
---------	------------

Packaging:

Packaging	Individually packaged, 100 by box
-----------	-----------------------------------

Mechanical Characteristics (Connectivity):

Storage Temperature Range	-40°C To +75°C
Operating Temperature Range	-10°C To +60°C

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards & Environmental Programs:

EU Directive 2011/65/EU (ROHS II)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	01/01/2013
MII Order #39 (China RoHS)	EUP 50
Safety Listing	ACMA

Suitability:

Suitability - Indoor	Yes
----------------------	-----

Transmission Characteristics (Connectivity):

Electrical Characteristics (Overall):

AX104696 Cable Assemblies - Breakout Kit - 12-Fiber

Notes (Overall):

Notes	This part comes with a printed label, an alcohol pad and instruction sheets. For additional information about this product visit our web site at http://www.belden.com .
-------	--

Product Family:

Revision Number: 0 Revision Date: 08-01-2014

© 2023 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.