


**NP 267**

**Belden® Digital Audio Cable**

Belden Brilliance® AES/EBU Digital Audio Cable, Part No. 1353A, is a robust single-pair Cat 5e patch cord that utilizes Belden's exclusive Bonded-Pair technology for outstanding reliability in both indoor and outdoor applications.



**Belden Brilliance AES/EBU Digital Audio Cables Provide Optimal Digital/Analog Performance and Installation Ease**

Belden Brilliance 1353A, a new Cat 5e digital audio single-pair cable, is ideal for use in professional and commercial audio applications. Since it is essentially 'single pair-Category 5e,' tested to 100 MHz, its low capacitance (15 pF/ft, 49 pF/m) makes it excellent for both analog and digital audio. It is especially valuable where small size, low weight, and high performance are required, and can be used anywhere a traditional analog or digital shielded pair might be employed, even where cabling may experience rough handling and harsh environmental conditions.

**Installation Efficiency**

This robust 100 ohm UTP with 24 AWG stranded (7x32) bare copper conductors is truly something new, filling a user-requirement gap that has previously gone unaddressed. Many installers routinely use Category 5e or Category 6 cables for audio applications. But, until now if you wanted a single Cat 5e pair, it was necessary to take a four-pair cable and laboriously separate out a pair. The availability of this new ready-to-use jacketed single pair eliminates those inconvenient steps, saving installation time and improving installation efficiency.

**Installable Performance®**

Belden's patented Bonded-Pair technology provides maximum ruggedness and consistent electrical properties during and after installation. During installation, cables are typically pulled, bent, and even kinked. All of these actions can alter the dimensions and physical properties of the cable, degrading its electrical performance. However, the Bonded-Pair design attaches the two wires together (without glue!) for a uniform conductor-to-conductor spacing. This helps the cable withstand the rigors of installation and maintain high performance.

The balanced nature of a twisted pair maximizes 'common mode rejection' and cancels out electromagnetic noise such as EMI, RFI and crosstalk from other pairs. Belden's Bonded-Pair design goes one better since it does not allow gaps to form between conductors so pairs are even more consistent in dimensions and therefore less likely to pick up noise from other sources.

This cable is UTP, a single 'unshielded twisted pair'. Having no shield and no drain wire virtually eliminates problems associated with shields, such as 'ground loops.' But, in applications that require a ground connection to work, such as phantom powered microphones or some intercom systems, this cable would not be appropriate.

## Not Just for Digital Use, But Analog Too, and More

As a bonus, the 1353A Single-pair Digital Audio Cable can be used for analog applications as well as digital. In general, in a digital cable it's the impedance that's the critical electrical parameter, not just capacitance as in analog cables. By nature of their design, Belden Digital Audio Cables have a low capacitance due to their high impedance, making them excellent analog cables. Even if your immediate needs happen to be strictly based on analog, installing an AES/EBU digital audio cable like Belden 1353A will give you the best possible analog audio service and "futureproof" your facility when you upgrade to digital.

For unbalanced applications such as base-band video, consumer unbalanced audio, or digital audio on coax (AES3-id or S/PDIF), the

use of baluns will allow the installer to use 1353A for those applications too. It will even carry up to six channels of broadband with its 100 MHz bandwidth, with appropriate baluns. For more information, consult the white paper "Video and UTP" in the technical papers section at [www.belden.com](http://www.belden.com)

## Outstanding Construction for Indoor/Outdoor Versatility

This innovative new product's jacket is made of a rugged matte-finish PVC, yet the cable is still highly flexible and very round. Overall nominal cable diameter is 0.126 in. so the minimum installed bend radius is 1.26 in. The insulation on the pair is polyolefin. Operating temperature range for Belden 1353A is -20°C to 60°C and this cable complies with NEC/(UL) CMR (riser) and CEC/(UL) CMG fire ratings.

## AES/EBU Digital Audio Cable TIA/EIA-568-B.2 Category 5e Patch Cable

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD		Nom. Imp. ( $\Omega$ )	Nom. Vel. of Prop.	Nom. Capacitance		Max. DCR ( $\Omega$ ) 100m	Max. DCR Unbal. (%)	Freq. (MHz)	Max. Atten. (db/ 100m)	Fitted Imped ( $\Omega$ )	Min. RL (dB)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm			pF/Ft.	pF/m							

**24 AWG** Stranded (7 x 32) Bare Copper Conductors • Bonded-Pairs

**Non Plenum • Polyolefin Insulation • PVC Jacket** (see colors below)

	300V RMS 1353A 	NEC:	1	500	152.4	5.5	2.5	0.126	3.20	100	70%	15	49	9.0	3.0	1	2.4	105±15	20.0	23.0	
		CMR		U-1000	U-304.8	9.0	4.1										4	4.9	100±15	23.0	23.0
		CEC:		U-1000	U-304.8	9.0	4.1										8	6.9	100±15	24.5	23.0
		CMG FT4		1000	304.8	9.0	4.1										10	7.8	100±15	25.0	23.0
																	16	9.9	100±15	25.0	23.0
																	20	11.1	100±15	25.0	23.0
															25	12.5	100±15	24.3	22.0		
															31.25	14.1	100±15	23.6	21.0		
															62.5	20.4	100±15	21.5	18.0		
															100	26.4	100±15	20.1	16.0		

### Jacket Colors Available:

Brown	Violet
Red	Gray
Orange	White
Yellow	Black
Lt. Blue	Military Green